



LOCATION		DATE
PREPARED BY		QUANTITY
COMMENTS		FIXTURE TYPE
CATALOG NUMBER		

Shaw LED Wrap Light SHAL Series

Features

Modern LED wrap can be used in various applications including corridors, kitchens and public spaces.

Construction

Housing is die-formed of 22-gauge steel. Mounting holes are included. Power supply connections are made inside the junction box (not included). Plastic molded endcaps.

Finish

Housing is finished in lighting grade white baked gloss enamel paint.

Diffuser

Frosted white acrylic diffuser.

Electrical

Direct wired for 120-277 VAC operation, 60 Hz.
Low voltage LED driver.

LED

Integrated LED modules capable of producing:
25W = 2000 source lumens
40W = 4000 source lumens
4000K (CCT), Rated for 50,000 Hrs., 80 CRI.

Certification:


cETLus listed for damp locations.
ENERGY STAR® Qualified

Limited Warranty:

This product is free from defective materials and workmanship for 5 years from original date of purchase and that under appropriate application, installation, operating conditions and when operated at rated voltage, will be free from failure.

Specifications and dimensions subject to change without notice.

**Limited Quantities Remain.
Consult Factory.**



Ordering Information:

White	LED	Source Lumens	CCT	L	W	H
SHAL052220L40MV	25W	2000	4000K	24"	5-1/4"	2-3/8"
SHAL054840L40MV	40W	4000	4000K	47-1/4"	5-1/4"	2-3/8"