



Sheridan LED Overbed SHB Series

Features

White linen patterned acrylic front panel provides a soft glow accent to this contemporary wall mount senior care overbed light. The satin nickel trim accents identify the graceful shape. The Sheridan provides both ambient and task light with a four way pull switch, standard (120 volt only). Top diffuser is clear, and bottom diffuser is frosted white acrylic.

Construction

The ballast/wiring channel is formed from 22-gauge steel and is provided with keyhole mounting slots and wiring access. An internal divider provides separate lamp compartments for controlled up light and down light. The decorative bands are stamped steel and glued to the diffuser. Fixture can mount horizontally only. Power connections can be made in the fixture wiring channel or in a standard junction box (not included).

Finish

All metal parts are finished in plated Satin Nickel or Champagne. Internal housing is finished in a lighting grade baked white enamel.

Diffuser

Diffuser is 0.070" thick matte white acrylic for the down light, clear frosted acrylic for up light, and a white linen pattern acrylic front. Frame mounts to electrical channel with two decorative screws.

Electrical

Input 120VAC / 60 Hz.
Not compatible with dimmers.
Integrated four position pull switch (on up, on down, on both, all off) and single pull switch for nightlight.

LED

Integrated LED modules capable of producing:
36W = 4050 source lumens
46W = 5400 source lumens
Rated for 50,000 hours, 3000K (CCT), 90 CRI.
Provides 50 footcandles of reading light over bed.

Certification

All fixtures are cETLus listed for indoor damp locations.

Options (Consult Factory)

120-277V universal voltage available without switch and nightlight.

Warranty

Limited warranty: This fixture is free from defects in materials and workmanship for a period of 5 years from date-of-purchase.

Specifications and dimensions
subject to change without notice..

Ordering Information:

Satin Nickel	Champagne	LED	Source Lumens	CCT	L	H	D	MC
SHB444000L30ENSN	SHB444000L30ENAC	36W	1350 up/2700 down	3000K	44-1/4"	4-5/8"	6-1/2"	29-1/8"
SHB565400L30ENSN	SHB565400L30ENAC	46W	1800 up/3600 down	3000K	56-1/4"	4-5/8"	6-1/2"	41-1/8"

LOCATION		DATE
PREPARED BY		QUANTITY
COMMENTS		FIXTURE TYPE
CATALOG NUMBER		



Satin Nickel



Champagne

