

Sheridan LED Sconce SHS Series

Features

Transitional style arm fixture with a top and bottom diffuser. Ideal use in hallways, entrances or anywhere general lighting is needed. Provides lighting in residential, commercial and hospitality applications. Fixture mounts standard to junction box (not included).

Construction

Back plate is die formed of 20-gauge steel. Standard mounting holes and hardware are included. The arms are tapered cast aluminum and require assembly to the backplate and wall. Power supply connections can be made inside a junction box (not included).

Finish

Backplate is finished in lighting grade white baked gloss enamel paint. Cast arm is finished in anodized Champagne or a plated Satin Nickel.

Diffuser

Diffuser is a hard backed white linen shade (LN) white linen acrylic (LA). Shade mounts to back plate with two screws. Top and bottom diffusers are .100" matte white acrylic.

Electrical

Input 120-277 VAC 60 HZ.

Compatible with residential (TRIAC/ELV) and commercial (0-10V) dimmers. TRIAC and ELV dimming only at 120 VAC.

LED

Fixture includes LED modules capable of producing: Single Arm - 9W = 700 source lumens Double Arm - 17W = 1400 source lumens Adjustable Choice 3000K, 3500K, 4000K (CCT). Rated for 50,000 Hrs. 90 CRI.


Certification

All fixtures are cETLus listed for indoor damp locations. ADA

Warranty

Limited warranty: This fixture is free from defects in materials and workmanship for a period of 5 years from date of purchase.

Specifications and dimensions subject to change without notice.






















MC - Mounting Center

Single Arm		Source					
Satin Nickel	Champagne	LED	Lumens	Adjustable CCT	H	W	D
CHCC61007LA ILIDCAL A	CHCUC10U21 VILLUVCI VI	014/	700	Z000K/ZE00K/4000K	10 1/2"	6 1/0"	7 1/2"

Double Arm		Source					
Satin Nickel	Champagne	LED	Lumens	Adjustable CCT	Н	W	D
SHS1218141 A ILIDSNI A	SHS1218141 A ILIDACI N	17\\\/	1400	3000K/3500K/4000K	18-1/2"	12-5/8"	3-1/2"