

Slim Round LED Surface Mount Disc Light SLMF Series

Features

This ultra low profile, flat back design, mimics the look of recessed lighting without the need for housings. Products can be used in various applications including corridors, closets, bath, showers, hallway, kitchen and anywhere general lighting is needed. Wall or ceiling mount.

Construction

Aluminum housing. Mounts to standard junction box (not included). Power supply connections must be made inside junction box. 6-3/8" - Mounting Center is 2-3/4" apart for J-box with mud ring style.

7-1/2" - Mounting Center is 3-1/2" apart for octagon J-box application only (without mud ring).



White finish.

Diffuser

Frosted acrylic.

Electrical

Direct wired, 120V AC with Driver-on-Board technology. Dimmable down to 10% of full scale with a 2-wire (Triac) or electronic low voltage (ELV) dimmer switch.

Lamping

Fixture includes a LED modules capable of producing: 10W = 640 delivered lumens, 785 source lumens 15W = 990 delivered lumens, 1380 source lumens 3000K (CCT). 50,000 Hrs. 90 CRI.

Certification

cETLus listed
Title 24/JA8 Compliant

Wet location rated for indoor use.

Outdoor wet location rated for covered ceiling mount applications ONLY (not recommended for any other outdoor use).

(not recommended for any other outdoor use).

Suitable for use in clothes closets when installed in accordance with the NEC 410.16 spacing requirements.

Warranty

Limited warranty: This fixture is free from defects in materials and workmanship for a period of 5 years from date-of-purchase.

Specifications and dimensions subject to change without notice.











SLMF04L30D1WH










SLMF06L30D1WH



Ordering Information:

White		Lumens	Lumens	ССТ	DIA.	D	MC
SLMF04L30D1WH	10W	640	785	3000K	6-3/8"	3/4"	2-3/4"
SLMF06L30D1WH	15W	990	1380	3000K	7-1/2"	1-1/8"	3-1/2"