



Sinclair LED Sconce SNS Series

LOCATION		DATE
PREPARED BY		QUANTITY
COMMENTS		
CATALOG NUMBER		Fixture Type



Features

Decorative sconce with a white acrylic diffuser and metal construction. Ideal use in hallways, entrances or anywhere general lighting is needed. Provides lighting in residential, commercial and hospitality applications. Meets ADA requirements. Fixture mounts to a 2" x 4" junction box (not included)

Construction

A combination of 22-gauge steel housing and aluminum die cast accent trim supporting fabricated diffuser. Rear housing is recessed and smaller than the front plate. Power supply connections must be made inside a junction box (not included).

Finish

Satin Nickel or black finish.

Diffuser

Frosted white acrylic.

Electrical

Input 120-277 VAC 60 HZ. Compatible with residential (TRIAC/ELV) and commercial (0-10V) dimmers. TRIAC and ELV dimming only at 120 VAC.

LED

Integrated LED modules capable of producing:
9W = 590 delivered lumens
18W = 1240 delivered lumens
Selectable 2700K, 3000K, 3500K, 4000K, 5000K (CCT).
50,000 hr. LED life, 90 CRI.




Certification

All fixtures are cETLus listed for indoor damp locations.
Title 24/JA8 Compliant
ADA

Warranty

Limited warranty: This fixture is free from defects in materials and workmanship for a period of 5 years from date of purchase.

**Specifications and dimensions
subject to change without notice.**



Ordering Information:

Black	Satin Nickel	LED	Delivered Lumens	Adjustable CCT	H	W	D
SNS0410LAJUDBK	SNS0410LAJUDSN	9W	590	2700K/3000K/3500K/4000K/5000K	10"	3-3/4"	3"
SNS0418LAJUDBK	SNS0418LAJUDSN	18W	1240	2700K/3000K/3500K/4000K/5000K	18"	3-3/4"	3"