

Sorrento LED Sconce SORS Series

Features

A decorative band with a white acrylic diffuser. Provides lighting in residential, commercial and hospitality applications. Meets ADA requirements. Fixture mounts to standard junction box (not included).

Construction

A 22-gauge shallow metal pan is made by stamping process and plated to provide a long lasting finish. An oblique diffuser is bonded with multiple acrylic panels and secured to decorative die-cast metal accent trim. Power supply connections must be made inside a junction box (not included).

Finish

Satin Nickel or Oakley Bronze*.

Diffuser

0.100" thick smooth matte white acrylic with irregular 5 facets.

Electrical

Input 120-277 VAC 60 Hz. 0.14A at 120 VAC. Compatible with residential (TRIAC/ELV) and commercial (0-10V) dimmers. TRIAC and ELV dimming only at 120 VAC.

LED

Integrated LED modules capable of producing: 17W = 1400 source lumens Adjustable Choice 3000K, 3500K, 4000K (CCT). Rated for 50,000 Hrs. 90 CRI.

Certification

All fixtures are cETLus listed for indoor damp locations. ADA

Warranty

Limited warranty: This fixture is free from defects in materials and workmanship for a period of 5 years from date-of-purchase.


Specifications and dimensions subject to change without notice.

DATE LOCATION PREPARED QUANTITY ΒY COMMENTS FIXTURE TYPE CATALOG NUMBER









Ordering Information:

Satin Nickel

Oakley Bronze* LED SORSO51914LAJUDSN SORSO51914LAJUDKB 17W

Lumens Adjustable CCT W 3000K/3500K/4000K 18-1/2" 4-3/4" 3-1/2"

*Special Order - consult factory for MOQ and lead time.

Source

1400