



Spring Low Profile Wrap SPRL LED Series (Adjustable CCT)

Features

This low profile, clean appearance, surface mounted wrap provides high light output with a clear prismatic lens. It can be used in various commercial and residential applications. Fixture mounts to a standard junction box (not included).

Construction

Housing is made from 22-gauge stamped steel and painted in lighting grade white. One of the end cap is designed to pivot with spring tension for ease of servicing the diffuser. Diffuser is supported by end caps. Power supply connections must be made inside a junction box (not included).

Finish

White

Diffuser

Acrylic diffuser is .060" thick prismatic diamond pattern.

Electrical

Input 120-277 VAC/60 HZ
Not compatible with dimmers.

LED

Integrated LED modules capable of producing:
2 ft. - 26W, 2400 source lumens
4 ft. - 40W, 3600 source lumens
4 ft. - 55W, 7300 source lumens
4000K (CCT), Rated for 50,000 Hrs., 80 CRI.

Certification

cETLus listed for indoor damp locations

Option for SPRL074873L40MV ONLY*

Emergency Battery Back-Up (add -BB to the end of the model number)

Warranty

Limited warranty: This fixture is free from defects in materials and workmanship for a period of 5 years from date of purchase.

Specifications and dimensions subject
to change without notice.

Ordering Information:

Cool White	LED	Source Lumens	CCT	L	W	D	MC
SPRL052424L40MV	26W	2400	4000K	24"	5-3/8"	2-3/8"	12-3/16"
SPRL054836L40MV	40W	3600	4000K	48"	5-3/8"	2-3/8"	36-3/16"
SPRL074873L40MV*	55W	7300	4000K	48"	6-1/2"	3"	36-3/16"

LOCATION		DATE
PREPARED BY		QUANTITY
COMMENTS		FIXTURE TYPE
CATALOG NUMBER		

