

Soho LED Pendant SSP Series



DATE

QUANTITY

FIXTURE TYPE



Features

Frosted glass cylinder pendant is suspended with an 9 ft. adjustable cord. Canopy mounts to a standard junction box (not included)...

Construction

The glass cylinder is 14" tall and 3-7/8" in diameter and held into place by three decorative studs. The canopy fits over a standard junction box. Power supply connections must be made inside a junction box (not included).

Finish

The canopy is plated in black or satin nickel.

Diffuser

Inner white glass cylinder is 0.14" thick.

Electrical

Input 120-277 VAC / 60 HZ. Compatible with residential (TRIAC/ELV) and commercial (0-10V) dimmers. TRIAC and ELV dimming only at 120 VAC.

LED

Integrated LED modules capable of producing: 15W = 1000 delivered lumens Selectable 2700K, 3000K, 3500K, 4000K, 5000K (CCT). Rated for 50,000 Hrs., 90 CRI.

Certification

All fixtures are ETL listed for indoor damp locations.

Warranty

Limited warranty: This fixture is free from defects in materials and workmanship for a period of 5 years from date of purchase.

Specifications and dimensions subject to change without notice.



LOCATION PREPARED

COMMENTS

CATALOG NUMBER

BY

Ordering Information:



