

Vera Task Lighting VRAU Series

Features

The VRAU Series low prowfile make it ideal for undercabinet lighting in kitchens. study area and displays. The housing is available in 5 different lengths, ranging from 9" to 40" to handle most application requirements. Linkable up to 200 watts. In addition the units can be direct wired, and attached to the cabinet with 2 captive mounting screws provide for a smoother installation. Multiple knockouts on the top and the back which offers maximum wiring flexibility.

Features:

- · BX/NM cable connector
- direct connector (included)

Construction

Fixture housing is made from extruded aluminum.

Finish

All exposed metal parts are post painted white.

Diffuser

White polycarbonate.

Electrical

Input 120V 60 Hz. This product provides a user selectable switch with 3 color choices - 2700K, 3000K & 4000K CCT respectively. The fixture is dimmable with most standard 2 wire (Triac) wall dimmers or an electronic low voltage dimmer switch (sold separately).

LED

Integrated LED type SMT array, non-replaceable arrays are used to create 2700K, 3000K or 4000K color temps. Rated to 75,000 hrs. 90 CRI.


Certification

Fixtures are cULus listed for indoor damp locations and carry a UL rating for undercabinet/convertible/linkable mounting. Title 24/JA8 Compliant

Warranty

Limited warranty: This fixture is free from defects in materials and workmanship for a period of 7 years from date-of-purchase.

Specifications and dimensions subject to change without notice.
















Ordering Information:

	Lumens								
Size	White	Туре	2.7K	3.0K	4.0K	LPW	L	W	D
9 in.	VRAU09WH	5W	290	300	295	60	9"	2-3/16"	1"
14 in.	VRAU14WH	9W	470	525	490	58.3	14"	2-3/16"	1"
22 in.	VRAU22WH	15W	820	915	865	61	22"	2-3/16"	1"
32 in.	VRAU32WH	18W	1020	1030	1000	57.2	32"	2-3/16"	1"
40 in.	VRAU40WH	23W	1315	1430	1400	62.2	40"	2-3/16"	1"

LPW based on 3000K color temperature



ACCESSORIES (ORDER SEPARATELY)

VRAC12WH 12" Interconnect cord VRAC24WH 24" Interconnect cord VRAC36WH 36" Interconnect cord VRAC48WH 48" Interconnect cord VRAC72WH 72" Interconnect cord VRAP60WH 60" Cord & Plug VRA-OCC

Occupancy sensor with 24" Cable