



LOCATION		DATE
PREPARED BY		QUANTITY
COMMENTS		FIXTURE TYPE
CATALOG NUMBER		

## LED Industrial Grade Vaportite (Adjustable CCT) VTL Series

### Features

Designed for applications requiring an industrial grade fixture that can be used where dirt, dust, humidity, moisture and cold temperatures are present. The polycarbonate housing is fully gasketed. Includes mounting brackets and water tight connector. Includes a set of metal closing clips and a set of plastic clips for coastal applications.



### Option

Emergency Battery Back-Up (model # with -BB)  
9.5VDC LiFeP04 battery, 8 Watts, 90 minute run time.

### Construction

Impact resistant grey polycarbonate housing. Continuous gasket offers secure seal against dust and moisture. Power supply connections can be made inside fixture wire way or in a junction box (not included).



### Finish

Grey polycarbonate.

### Diffuser

White polycarbonate.



### Electrical

Input 120-277 VAC / 60 Hz.  
0-10V dimming.

### LED

Integrated LED modules capable of producing:  
25W = 2800 source lumens, 2250 delivered lumens  
50W = 5500 source lumens, 4500 delivered lumens  
Adjustable CCT - 3000K/4000K/5000K  
Rated for 50,000 Hrs., 90 CRI.



### Certification

All fixtures are cETLus listed for indoor wet locations.

### Warranty

Limited warranty: This fixture is free from defects in materials and workmanship for a period of 5 years from date of purchase.

**Specifications and dimensions  
subject to change without notice.**



## Ordering Information:

Grey	LED	Source Lumens	Delivered Lumens	Adjustable CCT	L	W	D
VTL243500LAJD2	25W	2800	2250	3000K/4000K/5000K	24"	3-7/8"	3"
VTL476000LAJD2	50W	5500	4500	3000K/4000K/5000K	47"	3-7/8"	3"
VTL476000LAJD2-BB	50W	5500	4500	3000K/4000K/5000K	47"	3-7/8"	3"