



LOCATION		DATE
PREPARED BY		QUANTITY
COMMENTS		FIXTURE TYPE
CATALOG NUMBER		

Ideal LED Contemporary Oval PIDF Series

Features

Contemporary framed oval ceiling mount with satin nickel finish. Product can be used in various applications including corridors, baths, laundry rooms and kitchens. Fixture mounts to standard junction box (not included).

Construction

Housing is die-formed of 22-gauge steel. Standard mounting holes and hardware are included. Steel trim band is made of 20-gauge steel. Power supply connections must be made inside a junction box (not included).

Finish

Housing is finished in lighting grade white baked gloss enamel paint. Trim ring is satin nickel finish.

Diffuser

Diffuser is .080" thick vacuum formed smooth white acrylic.

Electrical

This unit is direct wired with constant current low-voltage electronic LED driver. 120-277V universal-voltage (non-dimmable) driver.

Lamping

Fixture includes LED modules capable of producing 32W-2900 source lumens. 4000K (CCT). 50,000 LED life. 80 CRI.

Certification

cETLus listed for damp locations.

Warranty

Limited warranty: This fixture is free from defects in materials and workmanship for a period of 5 years from date of purchase.

Specifications and dimensions
subject to change without notice.

Ordering Information:

Satin Nickel	LED	Source Lumens	CCT	L	W	D
PIDF172900L40MVSN	32W	2900	4000K	32"	17"	4"

